


Dealer



Coaxial Cable 同軸電線



施耐德電氣(香港)有限公司
客戶服務中心
電話：(852) 2579 9699
傳真：(852) 2811 1029
電郵地址：hk-ccc@hk.schneider-electric.com
網址：www.schneider-electric.com.hk

SEHK/CHK/SCS03

Schneider
Electric

施耐德電氣

Coaxial Cables

同軸電線



Product Features

- Applies to drop cable for CATV and MATV distribution
- Meet SCTE IPS-SP-001, UL1655, UL13 and UL444TEC DROP CABLE standards

Benefits

- Performance meets and greatly exceeds International Link of Channl specification standards
- World-class quality
- Compliant to industry standards of EIA, TIA, IEEE, ISO, ANSI, UL, CNAACL, TS008 & TS009, Australia & New Zealand 3080 and ISO 11801

產品特點

- 適用於CATV及MATV系統配線
- 符合SCTE IPS-SP-001，UL1655，UL13及UL444標準

優點

- 性能遠超國際規範標準
- 世界級的品質
- 符合EIA，TIA，IEEE，ISO，ANSI，UL，CNAACL，TS008和TS009，澳洲和新西蘭3080和ISO11801標準

Model Number 產品型號	CRG59305CMCC	CRG6305CMCC
Technical Information 技術資料		
Coaxial Cable 同軸線類別	RG59	RG6
AWG 美式線規	20	18
Insulation Material 絕緣材料	Skin Foamed PE 發泡 - 雙層聚乙烯	
Insulation Dimension 絕緣尺寸	3.66±0.08mm	4.57±0.08mm
Foild Shield 遮蔽箔	Al-mylar 導電鋁箔	
Braid Shield 遮蔽編網	Aluminium Wire 鋁線	
Construction 結構	16/4/0.16	
Coverage Area 覆蓋範圍	≥61%	
Outer Jacket 外皮	PVC	
Outer Jacket Thickness 外皮厚度	0.7	
Cable Diameter 線直徑	5.8±0.5mm	6.7±0.3mm
Electrical Characteristic 電氣特性		
Mutual Capacitance @1kHz 互感性@1kHz	53.1 pF/m	
Max Conductor DC resistance 最高直流電阻	161.4 Ω/km(@20°C)	102 Ω/km(@20°C)
Imepdence 阻抗	75Ω	